



WiFi Switching Cloud Keys & Gateways Camera Security Door Access Power Tech New I

Switching > [Pro Max 16](#)

Datasheet

- In The Box
- Marketing Images
- Installation Guide



Mechanical

Dimensions 325.1 x 160 x 43.7 mm (12.8 x 6.3 x 1.7")

Weight 1.95 kg (4.3 lb)

Enclosure material SGCC steel

Hardware

Management interface Ethernet In-Band

Networking interface	(12) GbE RJ45 ports (4) 1/2.5 GbE RJ45 ports (2) 10G SFP+ ports
Total non-blocking throughput	42 Gbps
Switching capacity	84 Gbps
Forwarding rate	62.496 Mpps
Power method	Type-C adapter
Power supply	5V, 25W
Max. power consumption	25W
LCM display	(1) 1.3" touchscreen
Button	Factory reset
Ambient operating temperature	-5 to 40° C (23 to 104° F)
Ambient operating humidity	10 to 90% noncondensing
Certifications	CE, FCC, IC

Switching Features

Layer 2 features	IGMP snooping STP / RSTP with priorities and port-level disable Port isolation Storm control Voice VLAN Port mirroring LACP port aggregation Multicast / broadcast rate limiting MAC address blocking Flow control 802.1X control Jumbo frames Proprietary loop protection DHCP snooping / guarding Egress rate limit LLDP-MED Port restricted by MAC Device isolation with ACLs
Layer 3 features	DHCP for locally-managed networks DHCP relay Inter-VLAN routing between networks on same switch

Static routing between local networks
Network isolation with ACLs

Etherlighting™

Ethernet	Locating Speed/link Native VLAN/network
SFP+	Locating Speed/link Native VLAN/network

Application Requirements

UniFi Network	Version 8.1.127 and later
----------------------	---------------------------

Stay in Touch

[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.